

Adhesive Reference

	Product	RH Limit ASTM 2170	Vapor Emission ASTM F1899	pH Limit	Weight (lbs) per Unit	Trowel Size and Usage Notes	Unit Size	Coverage per Unit	Recommended				TOLI®			C.I. TAKIRON								
									Wet or Flood Washed	Extreme Heat or Cold	Heavy Static Load	Custom Designs	Mature® Select™	Lightwood®/Kareina Asento®	Homogeneous Vinyl Tile	Nattice™ & Pathways (Interior)*	Nattice & Pathways (Exterior)	Tread & Risers (Interior)	Tread & Risers (Exterior)					
Adhesives	CBC® 5001 Acrylic	85%	6 lbs / 24 hours / 1,000 SF	10 pH	40.0	1/16 x 1/16 x 1/16 V-notch	4 Gallon	670-750 SF		◆		◆					P		P					
						1/16 x 1/16 x 1/16 V-notch	4 Gallon	720-800 SF														N		
						1/32 x 1/16 x 1/32 U-notch	4 Gallon	880-1,040 SF		◆		◆	P	P	P									
						1/32 x 1/16 x 1/32 U-notch	4 Gallon	1,200-1,400 SF					N	N	N									
Adhesives	EcoSpray U Universal Resilient	90%	N/A	11 pH	11.0	LVT, Sheet	6 cans/ctn	140-160 SF can 840-1,000 SF ctn			◆	◆	◆	◆			◆							
						HVT	6 cans/ctn	180-200 SF can 1,100-1,200 SF ctn			◆	◆			◆									
Adhesives	CBC 951 Epoxy	90%	8 lbs / 24 hours / 1,000 SF		29.0	1/32 x 1/16 x 1/32 U-notch	1 Gallon	175-225 SF	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆				
Tread Accessories	Opti-Tape 9.5" Width				7.3		1 roll/ctn	165 LF per roll											◆					
	CBC 800 Nose Caulk				1.7	Double Caulking Gun	13.5 oz. Tube	40 LF per tube		◆									◆	◆				
	MS 939 Sealant				1.0	Standard Caulking Gun	10 oz. Tube	45 LF per tube	◆	◆							◆	◆	◆	◆				

P = Porous surface
 N = Non-porous surface
 ◆ = Porous & non-porous surface
 * = Interior wet areas follow exterior instructions