

Commercial LVT

Product Characteristics

Standard Spec	ASTM 1700		
Classification	Class III Type A & B		
Nominal Dimensions/ Packaging	4" x 35.4" (100mm x 900mm) 30 pcs (29.2sf)/ctn. 6" x 35.4" (150mm x 900mm) 20 pcs (29.2sf)/ctn.		
Overall Thickness	3.0mm (0.120")		
Wear Layer Thickness	0.5mm (0.020")		
Recycled Contents Pre-Consumer Post-Consumer MR Credit 4.1	>35% 0-2% 18.5% (Sum of Post-Consumer + 1/2 Pre-Consumer)		
Warranty	Lightwood is covered by a limited 10-year warranty. Visit our website, www.cbcflooring.com, for complete details.		



Test Performance

ASTM F1700	Characteristic	Test Method	Requirement	Performance
	Thickness	ASTM F386	± 0.005", as specified	Passes.
	Wear Layer Thickness	ASTM F410	0.5mm (0.020") for commercial use.	Passes.
	Size	ASTM F2421	± 0.016" per linear foot	Passes.
	Squareness	ASTM F2421	0.010" max	Passes.
	Indentation	ASTM F1914	Avg. < 8%	Passes. (4.7% as tested)
	Dimensional Stability	ASTM F2199	0.020"/LF	Passes. (≤ 0.013"/LF as tested)
	Flexibility	ASTM F137	1" (25.4mm)	Passes. (6mm Mandrel as tested)
	Chemical Resistance	ASTM F925	No more than slight change in surface dulling, surface attack, or staining.	Passes.
	Resistance to Heat	ASTM F1514	ΔE ≤ 8.0	Passes. (ΔE ≤ 1.0 as tested)
	Resistance to Light	ASTM F1515	ΔE ≤ 8.0	Passes. (ΔE ≤ 2.0 as tested)
	Static Load Limit (@250psi)	ASTM F970	≤ 0.005"	Passes. (0.000" as tested)
Additional Tests	Static Load Limit (Modified)	ASTM F970	≤ 0.005"	1,000 psi. (0.000" as tested) 2,500 psi (0.003" as tested)
	Static Coefficient of Friction	ASTM D2047	≥ 0.5	ADA Compliant
	Critical Radiant Flux	ASTM E648	0.45 W/cm ² or more-Class I	Class I (> 0.45 W/cm ²)
	Smoke Generation	ASTM E662	450 or less	<450 (Flaming and Non-flaming)
	VOC Emissions	CA 01350	TVOC ≤ 0.5 mg/m ³	Passes. FloorScore Certified FS-03027

Lightwood® Product Information and Technical Data

Commercial LVT

PLANK (4" × 36")



7261E Bleached Maple



7262E Natural Maple



7671E Cedar Plank



1021 Honey Oak



7023 Medium Oak



7043 Red Oak



1022 Golden Oak



7681E Rustic Cherrywood



7283E Dark Cherrywood



3206E Natural Bamboo



3207E Carbonized Bamboo



7613 Medium Chestnut



3212E Brazilian Cherrywood



7281E Light Cherrywood



7282 Classic Cherrywood





1911E White Sycamore



7850E Classic Maple



7871E Cedar Plank



1916E American Cherry



7813E Medium Cherrywood



7881 Rustic Cherrywood



3516 Antique Plank



7865 Stained Spruce



7866 Blackened Spruce

CBC® Flooring Phone: (919) 230-8700

Website: www.cbcflooring.com E-Mail: technical@cbcflooring.com

04-22