

SECTION 09 65 19.23
RESILIENT TILE FLOORING

CSI 3-PART **SHORT-FORM** GUIDE SPECIFICATION
USE FOR OUTLINE OR DD SPECIFICATION ISSUES.
EDIT TO SUIT PROJECT

PART 1 - GENERAL

1.1 SUMMARY

- A. Work of this Section consists of resilient solid vinyl printed pattern tile flooring and accessories including, but not limited to:
 - 1. TOLI **Lightwood**
 - 2. Accessories
 - a. Adhesives
 - b. Cleaning solutions
 - c. Finish top coatings

RED NOTE: Specifier to closely coordinate applicable sections between concrete and other subfloor substrate finishes with floor covering.

1.2 SUBMITTALS

- A. Product Data per SECTION 013000 or 013300 and as follows: Submit manufacturer's printed descriptions of materials, components and systems, performance criteria, use limitations, recommendations, and installation information.
- B. Shop Drawings per SECTION 013000 or 013300 and as follows: Submit keyed location plans, plans indicating resilient sheet flooring type, layout, pattern direction, edge transitions, columns, doorways, enclosing partitions, built-in furniture, cabinets, cutouts, expansion and control joints, and attachment requirements.
- C. Samples per SECTION 013000 or 013300.
 - 1. Initial for Selection: Submit printed color charts, sample chains or Architectural Binder indicating manufacturer's complete range to determine color, texture, shape, and/or composition for each type of material finish.
 - 2. Final Selection: Submit two (2) 9" samples of each different type, color and pattern selected for acceptance.
- D. Quality Assurance Submittals per SECTION 014000: Test and Evaluation Reports, and Qualification Statements.

NOTE: Edit LEED Requirements below to suit project.

- E. Sustainable Design (USGBC LEED®) Submittals: Submit the following in accordance with the requirements of SECTION 018113, LEED REQUIREMENTS:
 - 1. LEED Credit MR, Materials & Resources. Submit completed LEED Submittal Templates, and other required paperwork as follows:
 - a. MR 4.1: Recycled Content: 10 Percent (post-consumer + 1/2 pre-consumer)
 - 1). Submit product data indicating percentage by weight of recycled content.
 - 2. LEED Credit EQ, Indoor Environmental Quality. Submit completed LEED Submittal Templates and required paperwork as follows:
 - a. EQ 4.1: Low Emitting Materials, Adhesives & Sealants, VOC Data
 - 1). Submit manufacturers' product data for construction adhesives and sealants, including printed statement of VOC content and MSDS Sheets.
 - b. EQ 4.3: Low Emitting Materials, Carpet and Resilient Flooring Systems
 - 1). Submit manufacturers product data for systems that includes printed statement of VOC content.

- F. Closeout Submittals per SECTION 017000 or 017800.
1. Sustainable Design Closeout Documentation: Submit completed USGBC LEED® worksheet templates for the following credits:
 - a. MR 4.1
 - b. EQ 4.1, EQ 4.3.

NOTE: Edit percentage below to suit scope of project.

- G. Maintenance Material Submittals - Extra Materials: Submit no less than five (5) percent additional full and unopened cartons of each type and pattern of plank used.

1.3 QUALITY ASSURANCE

- A. Regulatory Requirements
1. Fire-Test-Response Characteristics: As determined by testing identical products as follows by a qualified testing agency.
 - a. ASTM E648: Critical Radiant Flux Classification: Class I
 - b. ASTM E662: Smoke Density: 450 or less
- B. Qualifications:
1. Manufacturer: A company with a minimum ten (10) years' experience in manufacturing products or systems similar to those indicated for this Project and with a record of successful in-service performance. A single source manufacturer supplying both product and adhesive.
 - a. Company shall be ISO 9001 Certified
 - b. Company shall be ISO 14001 Certified.
 2. Installer / Applicator: Perform installation with skilled, experienced, and trained workmen with demonstrated ability to install TOLI products, supervised by trained personnel who shall have a minimum three (3) years successful experience in installations of similar size and scope.
 3. Testing Agency: An independent testing agency with the experience and capability to conduct the testing indicated, meeting requirements of ISO/IEC (International Organization for Standardization / International Electrotechnical Commission) Standard 17025 or ASTM E699 and ASTM E329.
- C. Source Limitations: Obtain primary flooring materials and adhesive through a single source from a single manufacturer.
1. Provide secondary materials, including patching and fill material, joint sealant, and repair materials, of type and from source recommended by manufacturer of primary materials.
- D. Field Samples per SECTION 014000: Provide field samples, dry laid, to demonstrate aesthetic effects of materials in situ, assisting the Architect and Owner in making final selections.

1.4 DELIVERY, STORAGE, AND HANDLING

- A. Delivery, Storage and Handling per industry and manufacturer guidelines, and SECTION 016000 requirements.

1.5 WARRANTY

- A. Manufacturer Warranty. Provide manufacturer's ten (10) year limited warranty to be free from defects in material and workmanship, under normal commercial use and service, to repair or replace all effected tiles including reasonable labor.

PART 2 - PRODUCTS

2.1 MANUFACTURER

- A. Manufacturers List: Subject to compliance with requirements, provide products by one of the following:

1. TOLI Corporation, a flooring manufacturer represented by CBC AMERICA LLC, 2000 Regency Parkway, Cary, NC 27518; Telephone: 919.230.8700; E-mail: technical@cbcflooring.com; website: www.cbcflooring.com
- B. Substitution Limitations: No substitutions permitted because of the specific attributes listed in sections 2.2, 2.3, and 2.4.
- C. Product Options
 1. Flooring Type:
 - a. TOLI **Lightwood** Plank Tile: Interior Floor Finish Class I per ASTM E 648
 - 1). Sizes: 4 X 35.4 x 0.120 inches (100MM X 900MM x 3MM)
6 X 35.4 x 0.120 inches (150MM X 900MM x 3MM)
 - 2). Color and Pattern: See [The Collection](#)
 2. Maintenance System Options:
 - a. Cleaner / Maintainer maintenance system
 - b. Conventional acrylic finish maintenance system
 3. Accessories
 - a. Underlayment leveling compound per Section 035416
 - b. Expansion joints per SECTIONS 079200 and 079513
 - c. CBC 5001 Acrylic Adhesive
 - d. CBC 951 Epoxy Adhesive
 - f. Cleaning solutions

2.2 DESCRIPTION

- A. TOLI **Lightwood** is a Class III, Type A & B, luxury vinyl tile (LVT), made from polyvinyl esters and inorganic fillers materials formed under heat and pressure, printed with a pattern, and cut to create resilient plank tile flooring in a variety of colors and patterns. Product to include a calculated recycled content of 18.5% including >35% pre-consumer.
- B. **Sustainability Characteristics**
 1. **USGBC LEED Rating:** Comply with project requirements intended to achieve the following Rating, as measured and documented according to the USGBC LEED® Green Building Rating System, Version indicated:

NOTE: Each LEED Version requires a different credit total to achieve the desired LEED Rating.
Note: Select one of the following Ratings:

- a. Rating: Certified
 - b. Rating: Silver
 - c. Rating: Gold
 - d. Rating: Platinum
2. Applicable LEED Credits: Performance requirements of the following LEED Categories and Credits apply to this Section and are met as follows:
 - a. **Materials & Resources (MR):**
 - 1). MR Credit 4.1 and 4.2:
 - a). TOLI Lightwood contains 0-2% post-consumer + ½ >35% pre-consumer, or 18.5% recycled content.
 - b. **Indoor Environmental Quality (EQ):**
 - 1). EQ Credit 4.1:
 - a). Acrylic Adhesive - CBC 5001 VOC: 0 g/L
 - b). Epoxy Adhesive - CBC 951 VOC: 0 g/L

2). **EQ Credit 4.4:**

- a). **TOLI Lightwood FloorScore Certified Low Emitting. Floor Score Certificate.**

2.3 MATERIALS

A. **Lightwood** Plank Tile per ASTM F1700: Class: III, printed film vinyl tile

1. Composition: Vinyl tile formulated from solid PVC with printed film pattern construction
2. Surface:
 - a. Type A, Smooth
 - b. Type B, Embossed
3. Thickness: 0.120 inch (3.0mm)
4. Edge: 15° finished 4-sided beveled edge.

NOTE: Select size required for project and delete those not chosen.

5. Size: 4 x 35.4 x 0.120 inches (100mm x 900mm x 3.0mm)
6. Size: 6 x 35.4 x 0.120 inches (150mm x 900mm x 3.0mm)
7. Color and Pattern: As selected by Architect from Manufacturer's standard collection.

2.4 ACCESSORIES

NOTE: Select one of the following leveling methods, deleting the one not chosen.

- A. Leveling and Patching Compound: Trowelable latex-modified, Portland cement-based formulation provided or approved by manufacturer for applications indicated.
- B. Self-Leveling Underlayment: Pourable latex-modified, Portland cement-based formulation provided or approved by manufacturer for applications indicated.

NOTE: Select one of the following adhesive types, deleting that not chosen.

NOTE: Select CBC 951 when expecting floors to be frequently washed or wet, or floors installed in extremely hot, cold or wet spaces, such as near outside entrances or freezer cases, or floors subject to heavy loads, including hospital beds, heavy carts, pallet jacks, rolling chairs, etc. CBC 5001 is suitable for most other applications.

- C. Acrylic Adhesive: CBC 5001, solvent-free, low odor, acrylic based, high tack type adhesive acceptable to floor tile manufacturer to suit floor tile product and substrate conditions indicated.
- D. Epoxy Adhesive: CBC 951, solvent-free, water-resistant, hard-setting, reactive, epoxy type adhesive acceptable to homogeneous vinyl tile manufacturer to suit floor tile product and substrate conditions indicated.

RED NOTE: CBC/TOLI does not warrant the compatibility and performance of TOLI Lightwood with non-CBC adhesives.

- E. Adhesive Equipment: Professional U-notched trowel (1/32 x 1/16 x 1/32 inch).
- F. Floor Finish Systems: Provide protective liquid maintenance product system as recommended by flooring manufacturer's most recent published Maintenance Product Guide.

PART 3 - EXECUTION

3.1 FIELD CONDITIONS

- A. Conditions and Measurements: Visit jobsite to verify installation conditions and floor measurements.
 1. Ambient Conditions per manufacturer's most recent published written recommendations, SECTION 017000 or 017100 or 017116.

3.2 EXAMINATION, PREPARATION, AND INSTALLATION

- A. Proceed with installation only after unsatisfactory conditions have been corrected.
 1. Verify conditions and test substrates as recommended to meet requirements.

- B. Properly prepare manufacturer acceptable substrates to accept flooring.
 - C. Install tiles per manufacturer's most recent published [Installation Guide](#).
 - D. Expansion Joints: Locate movement joints where indicated prior to installation of adhesive and tile.
 - E. Protect flooring from traffic for 48 hours after installation or per adhesive manufacturer's most recent published instructions to allow proper set up time.
- 3.3 CLEANING, MAINTENANCE AND PROTECTION
- A. Provide Progress Cleaning and Provide Final Cleaning per DIVISION 01 requirements.
 - 1. Waste management per DIVISION 01 requirements.
 - 2. Provide maintenance for installed product per manufacturer's most recent published [Maintenance Guide](#).

RED NOTE: Do NOT wet mop until adhesive has set.

- 3. Provide protection for installed product per manufacturer's written recommendations.
- 3.4 CLOSEOUT ACTIVITIES
- A. Substantial Completion Requirements per DIVISION 01 requirements: Closeout procedures, demonstration and training, and sustainable design closeout documentation.

END OF SECTION

RED NOTE: Be sure to obtain the latest version of this Guide Specification.
This Guide Specification is not a completed document ready for use. It must be edited, deleting, adding, or modifying text, as required to suit project requirements.
The professional stamping and the contracting parties of the Contract Documents are responsible for the accuracy of issued project specifications, including any use of this TOLI floor tile Guide Specification.

TOLI AND CBC AMERICA LLC SHALL NOT BE LIABLE FOR DAMAGES ARISING OUT OF THE USE OF THIS GUIDE SPECIFICATION.