


Mature® AdVantage

Product Information and Technical Data

Commercial Sheet with ClearGuard™ Anti-Viral Wear Layer




Product Characteristics

Standard Spec	ASTM 1303
Classification	Type I Grade 1
Backing Class	Class B
Nominal Dimensions	6' Wide x 66' Long (1828mm x 20m)
Roll Size	44 Square Yards
Overall Thickness	2.0mm (0.080")
Wear Layer Thickness	0.5mm (0.02")
Recycled Contents	
Pre-Consumer	>14.5%
Post-Consumer	>14%
MR Credit 4.1	21.25% (Sum of Post-Consumer + 1/2 Pre-Consumer)
Warranty	Mature AdVantage is covered by a limited 15-year warranty. Visit our website, www.cbcflooring.com , for complete details.



Test Performance

	Characteristic	Test Method	Requirement	Performance
ASTM F1303	Thickness	ASTM F386	$\geq 0.040''$	Passes. (0.080")
	Wear Layer Thickness - Grade 1 (Commercial)	ASTM F410	$\geq 0.020''$	Passes. 0.5mm (0.020") with additional reinforced urethane top coat.
	Wear Layer Composition - Type 1	Certificate of Compliance	$\geq 90\%$ binder	Passes. With embedded anti-viral properties.
	Indentation	ASTM F1914	$\leq 0.012''$	Passes. (0.004" as tested)
	Flexibility	ASTM F137	1/4 mandrel, no cracks or breaks	Passes.
	Chemical Resistance	ASTM F925	No more than slight change in surface dulling, surface attack, or staining.	Passes.
	Resistance to Heat	ASTM F1514	$\Delta E \leq 8.0$	Passes. ($\Delta E \leq 1.0$ as tested)
	Resistance to Light	ASTM F1515	$\Delta E \leq 8.0$	Passes. ($\Delta E \leq 1.0$ as tested)
	Static Load Limit (@175psi)	ASTM F970	$\leq 0.005''$	Passes. (0.001" as tested)
	Static Load Limit (Modified)	ASTM F970	$\leq 0.005''$	500 psi. (0.003" as tested) 750 psi. (0.005" as tested)
Additional Tests	Static Coefficient of Friction	ASTM D2047	≥ 0.5	≥ 0.6 ADA Compliant
	Critical Radiant Flux	ASTM E648	0.45 W/cm ² or more-Class I	Class I (> 0.45 W/cm ²)
	Smoke Generation	ASTM E662	450 or less	<450 (Flaming and Non-flaming)
	VOC Emissions	CA 01350	TVOC ≤ 0.5 mg/m ³	Passes. FloorScore Certified FS-03031
	Anti-Viral	ISO21702		Destroys >99% in 24 hours SIAA Reg. #: JP0612352A0001V

Mature® AdVantage

Product Information and Technical Data



Commercial Sheet with ClearGuard™ Anti-Viral Wear Layer



3047 Bronze Antique Oak



4001 Hemp Silken Oak



3039 Warm Aged Oak



3054 Natural Miller's Oak




3048 Light Chalked Oak




3038 Light Aged Oak




471 Honey Oak




451 Light Oak




452 Red Oak



531 Light Brazilian Cherry




773 Deep Vermont Maple




772 Classic Vermont Maple




741 Natural Maple




771 Light Vermont Maple



762 Stained Beechwood




3070 Natural Japanese Cypress




3063 Rising Walnut



4002 Shade Homestead Oak



4028 Sunset Kelley Walnut



4029 Autumn Chandler Walnut

Mature® AdVantage

Product Information and Technical Data



Commercial Sheet with ClearGuard™ Anti-Viral Wear Layer



4027 Cappuccino Satin Walnut




4008 Ashen Herringbone Oak



3031 Blanco Terra



3032 Naran Terra




3001 Dusk Mortar



3027 Dove Stone Cloud



3029 Beige Stone Cloud



3084 Nutmeg Linen




3083 Jute Linen



3078 Beige Micro Tweed



3076 Gray Micro Tweed




4072 Denim Micro Tweed



4049 Dune Shiroy Marble



4064 Buff Velvet Travertine



4053 Fiore Terrazzo



Organic/inorganic materials
infused into UV layer
JP0612352A0001V

- Reduces the number of specific viruses on the product by 99% or more.
- SIAA marking indicates products that have been quality-controlled and disclosed such information in accordance to the guidelines of the Society of International sustaining growth for Antimicrobial Articles based on the results evaluated by ISO21702.
- Complies with SIAA safety standards.
- Antiviral processing is not intended for the treatment or prevention of illnesses.
SIAA Reg. #: JP0612352A0001V

CBC® Flooring

Phone: (919) 230-8700

Website: www.cbcflooring.com

E-Mail: technical@cbcflooring.com

04-22

TOLI Corporation is ISO 9001 and ISO 14001 certified.

CBC® is a trademark of CBC America LLC.

TOLI®, the TOLI logo, and Mature® are trademarks of TOLI Corporation.